



earth friendly chemistry

www.epasia.net

E P™ BONDEX

Ad-Mixture for concrete & masonry

E P™ Bondex is an admixture with a stronger, longer lasting, acrylic composition for adding to cementitious mixtures delivering unequalled adhesion to existing substrates and gives better workability to the user.

With over 30% solid content EP™ Bondex means you can repair and patch up concrete and plastering even faster with no cracking.

EP™ Bondex is designed for floors, skim coats over old concrete and masonry surfaces. Used for repairing holes, cracks and resurfacing old concrete to give a smooth fresh surface, can be mixed with cement plaster, screeds and all masonry wet work.

EP™ Bondex is non-toxic, non-flammable, mixes easily, versatile and water-clean up of tools.

Theoretical Coverage: 4.5 litres mixes with 25 Kilo of sand and cement mixture. Coverage depends on thickness of coat and roughness of surface

Consists of: 5 ltr - 20ltr - 220 ltr – 1000ltr IBC

Shelf Life: 12 months minimum from date of manufacture when maintained in protected storage @ 5 – 38 °C.



easy to use eco-friendly non toxic non flammable non Hazardous
COATINGS - CLEANERS - DEGREASERS - WATERPROOFING SYSTEMS
no mixing no special equipment non hazardous easy to use

APPLICATION INSTRUCTIONS

Always test on surface prior to application.

SURFACE PREPARATION AND APPLICATION:

1. If applying to walls, wash all walls first with EP™ Eco-Kleen. Clean away all dust, grime and/or fungus.
2. Brush EP™ Bondex onto wall first to pre-prime or brush EP™ Bondex into area to be filled or repaired.
3. Apply mortar mix while area is still wet to give strength, durability and adhesion.

COVERAGE:

Approximately 4.5 litres of EP™ Bondex mixed with 25 kilograms of sand and cement mixture. E P™ Bondex can be diluted with water up to 70:30 then added to sand & cement mixture, the higher the ratio of E P™ Bondex mixed the faster the repairs will dry.

DO NOT STORE IN STRONG SUNLIGHT.

Maintain unused material in closed containers in protected storage



easy to use eco-friendly non toxic non flammable non Hazardous
COATINGS - CLEANERS - DEGREASERS - WATERPROOFING SYSTEMS
no mixing no special equipment non hazardous easy to use

EP™ BONDEX

100% ACRYLIC EMULSION FOR CEMENT BASED FORMULAS

KEY FEATURES AND BENEFITS:

- Fourth Generation low viscosity emulsion developed specifically for enhancing the strength, durability and adhesion of cement based products.
- Prevents screeding from developing air pockets and 'drum' sounds.
- Suitable for the formulation of conventional and light weight renders and coatings, waterproofing systems, patching and repair mortars, underlayment's and commercial flooring.
- Provides dramatic improvements in bonding liquid applications, especially under wet conditions.
- Replaces hacking and attaching wire mesh to walls before plastering painted surfaces
- E P™ Bondex dries quickly and hardens all cement repairs in less than 30 minutes.
- Formulated systems display the typical 100% acrylic benefit on exterior exposure, no degradation or colour development.



EP Borneo Sdn Bhd - No. 10 Jalan PJU 3/40 - Sunway Damansara
Petaling Jaya 87410 - Selangor, Malaysia - Tel: + 603 7885 0150
Fax: + 603 7885 0150 - Email: contactus@epasia.net

COATINGS - CLEANERS - DEGREASERS - WATERPROOFING SYSTEMS