



earth friendly chemistry
www.epasia.net

E P™ Wood Sealer

A unique formulation manufactured for effective treatment and preservation of all wood surfaces.

For industrial, commercial and residential use on all indoor and outdoor timber.

EP™ Wood Sealer is the most effective wood sealer on the market for waterproofing, fire and smoke treatment, deterring bugs and rot in all types of wood and is also non-flammable, non toxic, non hazardous and non-caustic.

E P™ Wood Sealer requires no mixing, easy to use and simple water-clean up of all tools.

Theoretical Coverage: One (1) litre covers between 9 – 12 square metres.

Application Method: Spray, brush or roll-on.

Packaging Size: 5 ltr - 20ltr - 220 ltr – 1000ltr IBC

Shelf Life: 12 months minimum from date of manufacture when maintained in protected storage @ 5 – 38 °C.



DO NOT STORE IN STRONG SUNLIGHT.

Maintain unused material in closed containers in protected storage

easy to use eco-friendly non toxic non flammable non Hazardous
no mixing no special equipment non hazardous easy to use
COATINGS - CLEANERS - DEGREASERS - WATERPROOFING SYSTEMS

APPLICATION INSTRUCTIONS

E P™ Wood Sealer

ALWAYS TEST ON SURFACES PRIOR TO APPLICATION:

NOTE: Use gloves and goggles to keep from getting in eyes and skin.

1. Wash surface with EP™ Eco-Kleen to remove all surface oils.
2. Clean with water and allow to dry
3. Apply one coat of E P™ Wood Sealer – apply sparingly.
4. Allow to dry – about 45 minutes depending upon weather conditions.
5. Wash all tools with water after completion.

Mixing: None required.

Thinning: None required.



EP Borneo Sdn Bhd - No. 10 Jalan PJU 3/40 - Sunway Damansara
Petaling Jaya 87410 - Selangor, Malaysia - Tel: + 603 7885 0150
Fax: + 603 7885 0150 - Email: contactus@epasia.net

easy to use eco-friendly non toxic non flammable non Hazardous
COATINGS - CLEANERS - DEGREASERS - WATERPROOFING SYSTEMS
no mixing no special equipment non hazardous easy to use